

6


5

4

3

2

1



LCC104001-XXX CONSISTS OF A CONTINUOUS LENGTH OF BULK CABLE

NOTES:

1. CONSTRUCTION:
CONDUCTOR: 26 AWG(7/0.16±0.008mm) STRANDED BARE COPPER
INSULATION MATERIAL: HDPE
DIA. 0.037 ±0.02 [0.93 ±0.05]
PAIRS: COLOR CODED SINGLES TWISTED INTO PAIRS
BINDER: MYLAR(POLYESTER), 25% OVERLAPPING
SHIELD(1): ALUMINUM/MYLAR(POLYESTER) FOIL SHIELD WITH 25% OVERLAPPING (ALUM OUTWARD)
DRAIN WIRE: 24 AWG STRANDED TINNED COPPER WIRE
SHIELD(2): TINNED COPPER BRAID, 65% COVERAGE NOM.
JACKET: LOW SMOKE ZERO HALOGEN (SEE COLOR CHART)
NOMINAL DIA: .236 ±0.008 [6.0 ±0.20]
2. PHYSICAL PROPERTIES:
STORAGE TEMPERATURE RANGE: -20°C TO +80°C
OPERATING TEMPERATURE RANGE: -20°C TO +80°C
3. ELECTRICAL PROPERTIES:
DIELECTRIC STRENGTH:500V AC/1MIN
INSULATION RESISTANCE(HDPE):100 MEGA OHMS-10M Min.@20°C
CONDUCTOR RESISTANCE:(26AWG):150 OHMS/KM Max.@20°C
4. JACKET PRINT:
"L-COM, INC WWW.L-COM.COM VERIFIED TO TIA/EIA-568-B.2
Cat 5e 26AWG LSZH SF/UTP ROHS WW/YY(week/year)
5. REGULATORY COMPLIANCE:
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION).
6. LSZH CHARACTERISTICS:
FLAME RATING: IEC60332-1
CORROSIVE GAS: IEC60754
SMOKE EMISSION: IEC61034

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

LC LG Rev-D5 Asize

6

5


4

3

2

1

REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	04/18/2025	BZHANG	WLI



CROSS-SECTIONAL VIEW

COLOR CODE

A1: ORANGE x WHITE/ORANGE
A2: BLUE x WHITE/BLUE
A3: BROWN x WHITE/BROWN
A4: GREEN x WHITE/GREEN

ITEM NUMBER	LENGTH (FEET)	COLOR	PACKAGING
LCC104001-WHT	1000	WHITE (RAL9003)	SPOOL
LCC104001-BLU	1000	BLUE (RAL5017)	SPOOL
LCC104001-GRY	1000	GREY (RAL7044)	SPOOL
LCC104001-BLK	1000	BLACK (RAL9005)	SPOOL
LCC104001-RED	1000	RED (RAL3027)	SPOOL

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS


TOLERANCES:	
X = ±2 [5]	FRACTIONS ± 1/32
XX = ±0.02 [0.5]	ANGLES ± 1°
XXX = ±0.005 [0.13]	

CABLE LENGTH TOLERANCES:	
≤12 [305]	±1 [25] / -0
>12 [305] ≤ 60 [1524]	±2 [51] / -0
>60 [1524] ≤ 120 [3048]	±4 [102] / -0
>120 [3048] ≤ 300 [7620]	±6 [152] / -0
>300 [7620]	±5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY
AND SUBJECT TO CHANGE WITHOUT NOTICE
UN-DIMENSIONED/NON-CRITICAL FEATURES
MAY VARY IN SIZE AND LOCATION
COLORS MAY VARY

L-com
an INFINIT® brand

Website: www.L-com.com
Phone: 1.800.341.5266 | 1.978.682.6936



INTERPRET ALL DIMENSIONS AND
TOLERANCES PER ASME Y14.5

SCALE	SHEET
NONE	1 OF 1

DESCRIPTION

C5E SF/UTP 4PR/26 STR LSZH 1K

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	43321	BZHANG	LCC104001	A